AMENDMENT UNDER 37 C.F.R. §1.115

	\cdot
RI	
BI Endi	26. (Twice Amended) A diode laser system, comprising:
2	a laser head assembly which generates an output beam, the laser head assembly including:
3	M modules which generate M laser beams, wherein each of said M laser beams
4	occupies a different wavelength band;
5	M-R dichroic [bandedge] filters, wherein each of said M-R dichroic [bandedge]
6	filters transmits at least a respective one of said M laser beams occupying a given
7	wavelength band and reflects all other of said M laser beams not occupying the given
- 8	wavelength band; and
9	an optical device which combines said M laser beams to thereby produce said output
10	beam,
11	wherein:
12	M and R are positive integers;
13	R - M is greater than or equal to 2; and
14	M is an integer ≥2.
12-	
B	31. (Twice Amended) A laser head assembly which generates an output beam including M
2	laser beams, comprising:
3	M modules generating M laser beams, wherein each of said M laser beams has a different



4

5

6

7

2

single wavelength; and

no more than M-2 dichroic [bandedge] filters, wherein each of said M-2 dichroic [bandedge] filters transmits a corresponding one of said M laser beams and reflects all other of said M laser beams;

wherein M is an integer > 2.



- 33. (Twice Amended) A method for generating a high energy laser beam, comprising:
- (a) generating P collimated laser beams, each of the P collimated laser beams having an

AMENDMENT UNDER 37 C.F.R. §1.115

B3	3
End	4

5

6

7

8

3

4

5

6

7

8

9

3

4

5

6

7

8

9

[unconstrained] wavelength within an Mth wavelength band;

- (b) repeating step (a) M times so as to produce MxP collimated laser beams grouped into M different wavelength bands; and
- (c) coupling said MxP collimated laser beams into an optical path to produce a high energy beam,

wherein M and P are integers ≥ 2 .



36. (Twice Amended) A diode laser system, comprising:

laser head assembly (LHA) which generates an output beam, the LHA including:

M modules generating M laser beams, wherein each of said M laser beams has a different single wavelength;

M-1 first dichroic [bandedge] filters defining an optical waveguide for directing all of said M laser beams into the optical path, wherein each of said M-1 [bandedge] dichroic filters transmits a corresponding one of said M laser beams and reflects all other said M laser beams; and

a fiber coupling device disposed adjacent to the optical path for collecting said M laser beams to thereby produce an output beam;

where M is an integer ≥ 2 .



40. (Twice Amended) A diode laser system, comprising:

first means for generating M first laser beams, wherein each of said M first laser beams has a different single wavelength;

M-l first filter means defining a first optical waveguide for directing all of said M first laser beams into a first optical path, wherein each of said M-l filter means transmits a corresponding one of said M first laser beams and reflects all other said M first laser beams;

second means for generating M second laser beams, wherein each of said M second laser beams has a different single wavelength;

M-1 second filter means defining a second optical waveguide for directing all of said M

4

5

6

7

8

9

AMENDMENT UNDER 37 C.F.R. §1.115

10	second laser beams into a second optical path, wherein each of said M-1 second filter means
11	transmits a corresponding one of said M second laser beams and reflects all other said M second
12	· laser beams;
13	polarization combining means disposed at the intersection of said first and second optical
14	paths for coupling said M first and said M second laser beams into said second optical path to
15	thereby produce 2M polarization coupled laser beams; and
16°	fiber coupling means disposed adjacent to said second optical [oath] path for collecting said
17	2M polarization coupled laser beams to thereby produce an cutout laser beam,
18	wherein M is a integer ≥ 2 .
1	41. (Twice Amended) A method for generating a high energy laser beam, comprising:
2	(a) generating P collimated laser beams, each of the P collimated laser beams having an
3	[unconstrained] wavelength within an Mth wavelength band:

- (b) repeating step (a) M times so as to produce MxP collimated laser beams grouped into M different wavelength bands;
 - (c) coupling said MxP collimated laser beams into an optical [oath] path; and
- (d) coupling said MxP collimated laser beams into an ith optical fiber to thereby produce a corresponding ith output laser beam, where i = l to N;
- where M, N and P are positive integers and both M and $P \ge 2$.

REMARKS

Claims 1-41 will be pending in the application. In the Amendment, claims 25, 26, 31, 33, 36, 40, and 41 are amended for clarity. It is respectfully submitted that the instant amendment does not introduce new matter into the above-identified application.